

Vasario<sup>™</sup> Series Product Specifications

## **Electronically Operated (Media)**

| 1416 Model  |  |  |                         |
|---|--|--|-------------------------|
|   | <b>Dimensions:</b><br>(width x depth x height) | 13.8 x 16.3 x 3.5 inches   | Shipping weight: 16 lbs |
| Removable Coin T  | ray  |  |                         |
|   | <b>Dimensions:</b><br>(width x depth x height) | 12.7 x 11.7 x 2.2 inches   |                         |
|   | Part Number:                                   | VPK—15B—1A-BX  |                         |
| Removable Till Co   | ver  |  |                         |
|   | <b>Dimensions:</b><br>(width x depth x height) | 12.7 x 10.4 inches   |                         |
|   | Part Number:                                   | VPK—14B—3A-BX  |                         |
| Features –  | 1416 Model                                     |  |                         |
| - Black with a painted steel drawer front   |  | - 4 bill, 5 coin till (Qty 2) with coated wire bill hold downs                               |                         |
| <ul> <li>Tested to last beyond 1 million transactions</li> <li>Removable till cover with keyless latching mechanism</li> <li>Single 5 media slot</li> </ul> |  | <ul> <li>Under till storage area</li> <li>Closed and latched drawer status switch</li> </ul> |                         |
| Interface —   |  |  |                         |

485 485 USB Pro Lite<sup>™</sup> USB Serial Emulation with Detachable USB Cable

## **Operating Environment**

Storage Temperature $-30^{\circ}C$  to  $+50^{\circ}C$  ( $-22^{\circ}F$  to  $+122^{\circ}F$ )Operating Temperature $0^{\circ}C$  to  $+40^{\circ}C$  ( $+32^{\circ}F$  to  $+104^{\circ}F$ )

Relative Humidity 10% to 95% (non-condensing)

## Accessories

See our Standard Accessories Guide or contact your APG representative for options.1. Tills2. Latching, keyless till covers3. Under counter mounting brackets

## Warranty

One (1) year limited warranty. A full warranty statement is available online at www.cashdrawer.com/warranty.

M-43-111 Rev. I