


# MANUFACTURING/WIRING NOTES:

TEST UNIT I/FACE - S.I.U.

# CASH BASES



**NCD INTERFACE Mk2  
'JUMPERS' TO BE CONNECTED  
AS SHOWN TO GIVE :-**

**24/36 volt operation  
Signal With Drawer Open**

Part Number 70182  
RJ12 PLUG

VIEW ON PLUG  
MATING FACE



Pin 1 - Bl	- Ground	Reference Only
Pin 2 - Yw	- Solenoid	
Pin 3 - Gn	- Microswitch	
Pin 4 - Rd	- Solenoid +	
Pin 5 - Bk	-----	
Pin 6 - Wh	- Microswitch	

21825-015 = 1.5 Metre Long Cable  
21825-030 = 3.0 Metre Long Cable

Part Number 70182  
RJ12 PLUG

VIEW ON PLUG  
MATING FACE



Pin 1 - Bl	- Ground	Reference Only
Pin 2 - Yw	- Solenoid	
Pin 3 - Gn	- Microswitch	
Pin 4 - Rd	- Solenoid +	
Pin 5 - Bk	-----	
Pin 6 - Wh	- Microswitch	

(EPSON TM I/FACE 24v SIGNAL DRAWER OPEN)

REVISION/DATE	B 17/01/01					TOLERANCES	TITLE	DRG.NO.	REV
ECP No	ECP 6030					LENGTHS BELOW 1m TO BE -0; +5mm	WIRING DIAGRAM CONCEPT	CON-001	B
DRAWN BY	PK					LENGTHS 1-2m TO BE -0; +10mm			
CHECKED BY						LENGTHS ABOVE 2m TO BE -0; +15mm			
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED		FIRST USED ON	SHT. 1 OF 1

C

No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd. Newhaven, East Sussex.

Refer to Cash Bases for Latest Issue