


MANUFACTURING/WIRING NOTES:

TEST UNIT I/FACE - S.I.U.


CASH BASES



**NCD INTERFACE Mk2
'JUMPERS' TO BE CONNECTED
AS SHOWN TO GIVE :-**

**12 volt operation
Signal With Drawer Open**

Part Number 70182
RJ12 PLUG




VIEW ON PLUG
MATING FACE



Pin 1 - Bl	- Ground	Reference Only
Pin 2 - Yw	- Solenoid	
Pin 3 - Gn	- Microswitch	
Pin 4 - Rd	- Solenoid +	
Pin 5 - Bk	-----	
Pin 6 - Wh	- Microswitch	

21825-015 = 1.5 Metre Long Cable
21825-030 = 3.0 Metre Long Cable

Part Number 70182
RJ12 PLUG



VIEW ON PLUG
MATING FACE



Pin 1 - Bl	- Ground	Reference Only
Pin 2 - Yw	- Solenoid	
Pin 3 - Gn	- Microswitch	
Pin 4 - Rd	- Solenoid +	
Pin 5 - Bk	-----	
Pin 6 - Wh	- Microswitch	

(EPSON TM I/FACE 12v SIGNAL DRAWER OPEN)

REVISION/DATE	A 11/09/00	B 17/01/01	B 14/10/2010			TOLERANCES	TITLE	DRG.NO.	REV
ECP No		ECP 6030	20965			LENGTHS BELOW 1m TO BE -0; +5mm	CONCEPT INTERFACE EPSON 12V SDO	CON-009	C
DRAWN BY	PK	PK	MJ			LENGTHS 1-2m TO BE -0; +10mm			
CHECKED BY						LENGTHS ABOVE 2m TO BE -0; +15mm		FIRST USED ON	SHT.1 OF
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED			1

No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd. Newhaven, East Sussex.