


MANUFACTURING/WIRING NOTES:


TEST USING CBTI004 WITH BOX CBTU002
FOR 24V

Ⓑ USE CBTI122 WITH BOX CBTU001
FOR 12V

CASH BASES




SOLENOID
70390B050



RATING
12/24V 13W

9 WAY 'D' TYPE PLUG
70017

+
HOOD 70411



H9SRXXXM062AA

Ⓓ 70135 STR.RELIEF

HOUSING Pt.No.70426
PIN Pt.No.70429
No.of pins 4

HOUSING Pt.No.70427
PIN Pt.No.70428
No.of pins 4

4 BL
3 VT
2 GY
1 YW

RD 4
OR 3
BK 2
BL 1

PUSH-ON CONNECTOR

Part Number 70377


Qty 3

MICROSWITCH

70159

BN
OR
GN

SIGNAL
WITH
DRAWER
OPEN/CLOSED



VIEW ON SOLDER SIDE

PIN 1 - BL (SOL+)
PIN 2 - VT (WHITE) (SOL)
PIN 3 - BK NOT CONNECTED
PIN 4 - OR (MSW D/O)
PIN 5 - GN (MSW D/C)
PIN 6 - YW (SOL)
PIN 7 - GY (SOL)
PIN 8 - RD NOT CONNECTED
PIN 9 - BN (MSW COM)
DRAIN WIRE TO SHELL

70194 TERMINAL RING

WColour SCREEN

Ⓒ NOTE: FOR LEADS OF 1.5MTRS & ABOVE
USE DUA-M31

REVISION/DATE	F 22/11/2010					TOLERANCES	TITLE	Ⓔ DRG.NO.	REV
ECP No	10747					LENGTHS BELOW 1m TO BE -0; +5mm	03 FLIP LID INTERFACE	DUA-M24	F
DRAWN BY	DMJ					LENGTHS 1-2m TO BE -0; +10mm	12/24V S.D.C/O.	FIRST USED ON	
CHECKED BY	333					LENGTHS ABOVE 2m TO BE -0; +15mm		SHT.1 OF	1
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED			

Ⓒ No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd. Newhaven, East Sussex.