

MANUFACTURING/WIRING NOTES:



TEST USING CBT1004 WITH BOX CBTU002
FOR 24V
ⓑ USE CBT1122 WITH BOX CBTU001
FOR 12V

CASH BASES



9 WAY 'D' TYPE PLUG
70017

HOOD 70411



VIEW ON SOLDER SIDE

PIN 1 - BL (SOL+)
PIN 2 - VT (WHITE) (SOL)
PIN 3 - BK NOT CONNECTED
PIN 4 - OR (MSW D/O)
PIN 5 - GN (MSW D/C)
PIN 6 - YW (SOL)
PIN 7 - GY (SOL)
PIN 8 - RD NOT CONNECTED
PIN 9 - BN (MSW COM)
DRAIN WIRE TO SHELL

H9SRXXXM062AA

70135 STR.RELIEF

HOUSING Pt.No.70426
PIN Pt.No.70429
No.of pins 4

HOUSING Pt.No.70427
PIN Pt.No.70428
No.of pins 4

4BL
3VT
2GY
1YW

RD 4
OR 3
BK 2
BL 1

PUSH-ON CONNECTOR

Part Number 70377
Qty 3

MICROSWITCH
70159

BN
OR
GN

SIGNAL
WITH
DRAWER
OPEN/CLOSED

70194 TERMINAL RING

WColour SCREEN

SOLENOID
70390B050

RATING
12/24V 13W

Ⓒ NOTE: FOR LEADS OF 1.5MTRS & ABOVE
USE DUA-M31

REVISION/DATE	A 06/05/99	B 04/08/99	C 07/09/01	D 11/03/04	E 18/2/2008	TOLERANCES	TITLE	DRG.NO.	REV
ECP No		ECP5210	UPDATED	ECP8543	10747	LENGTHS BELOW 1m TO BE -0; +5mm	WIRING DIAGRAM	DUA-M24	E
DRAWN BY	JAR	JAR	PK	PK	DMJ	LENGTHS 1-2m TO BE -0; +10mm	MODULAR 03	FIRST USED ON	
CHECKED BY						LENGTHS ABOVE 2m TO BE -0; +15mm		SHT.1 OF	1
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED			

Ⓒ No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd. Newhaven, East Sussex.