

MANUFACTURING/WIRING NOTES:

TEST USING CBTI004 WITH BOX CBTU002
FOR 24V
USE CBTI122 WITH BOX CBTU001
FOR 12V

CASH BASES



SOLENOID
70402B050

RATING
12/24v 24W
6/24 ohms


9 WAY 'D' TYPE PLUG

HOOD 70411

H8SRXXXM002AD

70135 STR. RELIEF

70017
CONNECTOR



VIEW ON SOLDER SIDE

PIN 1 - BL (SOL+)
PIN 2 - RD (SOL)
PIN 3 - BK NOT CONNECTED
PIN 4 - OR (MSW D/O)
PIN 5 - GN (MSW D/C)
PIN 6 - YW (SOL)
PIN 7 - WH (SOL)
PIN 8 - NOT USED
PIN 9 - BN (MSW COM)
DRAIN WIRE TO SHELL

HOUSING Pt.No.70426
PIN Pt.No.70429
No.of pins 4

HOUSING Pt.No.70427
PIN Pt.No.70428
No.of pins 4
RD 4
OR 3
BK 2
BL 1

HEAT SHRINK SLEEVING

WColour GN

WColour OR

WColour BN

70460

SIGNAL
WITH
DRAWER
OPEN/CLOSED

WColour SCREEN

70194 TERMINAL RING

FOR FITTING
MICROSWITCH SEE
TSD-050 FOR CORRECT
TORQUE SETTINGS ^(B)

REVISION/DATE	A 26/06/08	B 14/10/2009	C 23/11/2010			TOLERANCES	TITLE	DRG.NO.	REV
ECP No	P 4864	20308	20965			LENGTHS BELOW 1m TO BE -0; +5mm	SPECIAL FLIPLID I/FACE	DUA-M35	C
DRAWN BY	MJ	MJ	MJ			LENGTHS 1-2m TO BE -0; +10mm	12/24V S.D.O/C.		
CHECKED BY						LENGTHS ABOVE 2m TO BE -0; +15mm		FIRST USED ON	SHT.1 OF 1
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED			

©

No part of this drawing may be reproduced or transmitted by any means, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd, Newhaven, East Sussex.