

MANUFACTURING/WIRING NOTES:

- TEST USING CBTI004 WITH BOX CBTU002 FOR 24V
 (B) USE CBTI122 WITH BOX CBTU001 FOR 12V

CASH BASES



SOLENOID
70311B050

RATING
12/24V 50%

HOUSING Pt.No.70426
PIN Pt.No.70429
No.of pins 4

HOUSING Pt.No.70427
PIN Pt.No.70428
No.of pins 4
4BL
3VT
2GY
1YW
RD 4
OR 3
BK 2
BL 1

9 WAY 'D' TYPE PLUG

HOOD 70411

70017 CONNECTOR

H9SRXXXR062AA


70136 STR.RELIEF

PUSH-ON CONNECTOR
Part Number 70377
Qty 3

MICROSWITCH
70159

BN
GN
OR

SIGNAL
WITH
DRAWER
OPEN/CLOSED



VIEW ON SOLDER SIDE

- (D)
 PIN 1 - BL (SOL+)
 PIN 2 - VT (WHITE) (SOL)
 PIN 3 - BK NOT CONNECTED
 PIN 4 - OR (MSW D/O)
 PIN 5 - GN (MSW D/C)
 PIN 6 - YW (SOL)
 PIN 7 - GY (SOL)
 PIN 8 - RD NOT CONNECTED
 PIN 9 - BN (MSW COM)
 DRAIN WIRE TO SHELL

70194 TERMINAL RING

WColour SCREEN

(C) NOTE: FOR LEADS OF 1.5 MTRS. & ABOVE
USE DUA-R06

REVISION/DATE	A 10/05/99	B 04/08/99	C 18/02/00	D 24/03/00	E 18/2/2008	TOLERANCES	TITLE	DRG.NO.	REV
ECP No		ECP 5210	REDRAWN	REDRAWN	10747	LENGTHS BELOW 1m TO BE -0; +5mm	WIRING DIAGRAM	DUA-R02	E
DRAWN BY	JAR	JAR	PK	PK	DMJ	LENGTHS 1-2m TO BE -0; +10mm	REMOTE		
CHECKED BY						LENGTHS ABOVE 2m TO BE -0; +15mm			
APPROVED BY						ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED		FIRST USED ON	SHT. 1 OF 1

(C) No part of this drawing may be reproduced or transmitted by any firm, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd. Newhaven, East Sussex.