


IF IN DOUBT - ASK


NCR-01 SPEC

SOLENOID
70279A050

RATING
24V 24 Ohm




VIEW ON PLUG
MATING FACE



PIN 1	BL (GROUND)
PIN 2	YW SOL
PIN 3	GN M/SW D/O
PIN 4	RD SOL +
PIN 5	BK (NOT CONNECTED)
PIN 6	WH M/SW COM

H6SFXXXR024AD
OR
H6SFXXXR024AW (E)

70215 STR.RELIEF



HOUSING 70426
PIN 70429 (2)

4RD
3
2
1YW

HOUSING 70427
PIN 70428 (2)

RD 4
3
2
RD 1

(C)

PUSH-ON CONNECTOR

MICROSWITCH
70159

SIGNAL
WITH
DRAWER
OPEN

WH
GN

WColour DRAIN

70194 TERMINAL RING

WColour BL

E) ALTERNATIVE (BLACK) HARNESS ADDED

E	21711	19/5/2011	MJ	UNSPECIFIED TOLERANCES		WIRING COLOUR CODES		CASH BASES 		Cash Bases Ltd. Newhaven, East Sussex BN9 0LA United Kingdom	Tel: +44 (0)1273 616300 Fax: +44 (0)1273 512010 www.cashbases.co.uk
---	---	---	---	LENGTHS BELOW 1 m TO BE - 0; + 5 mm		DRAWN MJ	BL = BLUE	WH = WHITE	TITLE SLIDEOUT I/FACE EPSON 24V [®] S.D.O. WITH FLYWHEEL DIODE	DRAWING NUMBER EPS-R01D	REV E
---	---	---	---	LENGTHS 1 - 2 m TO BE - 0; + 10mm			YW = YELLOW	OR = ORANGE			
---	---	---	---	LENGTHS ABOVE 2 m TO BE - 0; + 15mm			GN = GREEN	VT = VIOLET			
REV	ECP No	DATE	NAME			DATE 18/5/2011	RD = RED	GY = GREY			
PROD. ENG.		APPROVED BY:	CHECKED BY:	THIRD ANGLE PROJECTION TO BS8888. ALL DIMS IN mm				DO NOT SCALE			
© No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without prior permission of Cash Bases Ltd, Newhaven, East Sussex.											

