

MANUFACTURING/WIRING NOTES:

TEST @ 24V SDO USING
CBTU002 WITH CBT1172 ⑥

NCR-01 SPEC


IF IN DOUBT - ASK

SOLENOID
70279A050

RATING
24V 24 Ohm

70182
RJ12 PLUG

VIEW ON PLUG
MATING FACE



PIN 1 BL (GROUND)
PIN 2 YW SOL
PIN 3 GN M/SW D/O
PIN 4 RD SOL +
PIN 5 BK (NOT CONNECTED)
PIN 6 WH M/SW COM

H6SFXXXR024AD
OR
H6SFXXXR024AW ⑤

70215 STR.RELIEF

BACK e.m.f.
GF1D Diode

HOUSING 70426
PIN 70429 (2)
4RD
3
2
1YW

HOUSING 70427
PIN 70428 (2)
RD 4
3
2
RD 1 ③

PUSH-ON CONNECTOR
70377 (2)

MICROSWITCH
70159

SIGNAL
WITH
DRAWER
OPEN

WColour DRAIN

70194 TERMINAL RING

WColour BL


⑤ ALTERNATIVE (BLACK) HARNESS ADDED

REV	ECP No	DATE	NAME
PROD. ENG.	APPROVED BY:	CHECKED BY:	

UNSPECIFIED TOLERANCES

LENGTHS BELOW 1 m TO BE - 0; + 5 mm
LENGTHS 1 - 2 m TO BE - 0; + 10mm
LENGTHS ABOVE 2 m TO BE - 0; + 15mm

THIRD ANGLE PROJECTION
TO BS8888. ALL DIMS IN mm



DO NOT SCALE

DRAWN
MJ

DATE
18/5/2011

FIRST USED ON

WIRING COLOUR CODES

BL = BLUE WH = WHITE
YW = YELLOW OR = ORANGE
GN = GREEN VT = VIOLET
RD = RED GY = GREY
BK = BLACK

CASH BASES



Cash Bases Ltd.
Newhaven,
East Sussex BN9 0LA
United Kingdom
Tel: +44 (0)1273 616300
Fax: +44 (0)1273 512010
www.cashbases.co.uk

TITLE
SLIDEOUT I/FACE EPSON 24V ⑥
S.D.O. WITH FLYWHEEL DIODE

DRAWING NUMBER

EPS-R01D

REV

F

© No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without prior permission of Cash Bases Ltd. Newhaven, East Sussex.