

MANUFACTURING/WIRING NOTES:

TEST USING CBT1138
TEST AT 12V

MICROS 8700 I/F



CASH BASES



SOLENOID
70045A050

RATING
12V 50%

4PIN DIN PLUG
Connector Part Number 70022



VIEW ON
SOLDER SIDE

- (B) PIN1= RD SOL +
PIN2= BL SOL
PIN3= BK MSW COM
PIN4= WH MSW D/C
GREEN CONNECTED TO SHELL

H6URXXXR007AA

70065 STR.RELIEF

HOUSING Pt.No.70426
PIN Pt.No.70429
No.of pins 2

4RD
3
2
1 BL

HOUSING 70427
PIN 70428 (2)

RD 4
3
2
RD 1

PUSH-ON CONNECTOR
70377 (2)

MICROSWITCH
70159

BK
WH

SIGNAL
WITH
DRAWER
CLOSED

70194 TERMINAL RING

WColour GREEN

REVISION/DATE	A 17/05/99	B 18/03/04	C 31/08/07
ECP No		8558	10585
DRAWN BY	GIL	PK	DMI
CHECKED BY			
APPROVED BY			

TOLERANCES

LENGTHS BELOW 1m TO BE -0; +5mm
LENGTHS 1-2m TO BE -0; +10mm
LENGTHS ABOVE 2m TO BE -0; +15mm
ALL DIMENSIONS IN mm UNLESS
OTHERWISE STATED

TITLE

WIRING DIAGRAM
REMOTE

DRG.NO.

MIC-R03

REV

C

FIRST USED ON

SHT. 1 OF

1

(C) No part of this drawing may be reproduced or transmitted by any form, or in any means including photocopying and recording, without the prior permission of Cash Bases GB Ltd, Newhaven, East Sussex.